



## PRODUCT TECHNICAL SHEET

30 June 2024

### 125-2

#### 2 x 250W PA Amplifier

Designed for piped systems, it is able to provide an RMS power of 2x125W with both 4 Ohm and 70V/100V output.

Each channel has independent balanced XLR input and independent volume control. A selector allows you to choose the mode of use between MONO and DUAL. A filter can be operated for cutting high/low.

Each channel has independent LED indicators for signal, 4 Ohm, 70V, 100V and Pro.

Matrix	No
Max power	500
RMS power	2 x 125W
4 Ohm max power	500 W
8 Ohm max power	250W
Input impedance	70V, 100V
Impedance	4 Ohms
Multi zone	No
Phantom Key	No
Cooling fan	1 fan
Rack space	2U
Input connectors	XLR
Output connectors	screw terminal
Line inputs	2
Mic inputs	0
Constant voltage	70 - 100V compatible
S/N ratio	>95dB
Frequency response	L/H cut off 20Hz - 20 KHz
Color	black
Weight	6,9
Product dimensions	435 x 88 x 340mm



4Ω 70 100 VOLT 19" RACK

Puoi trovare articoli correlati, accessori ed aggiornamenti su:

[www.karmaitaliana.it](http://www.karmaitaliana.it)

Inoltre potrai scaricare i nostri cataloghi in formato PDF per:

- DeeJay - Mixer & Disco Light - Microfoni e raddiomicrofoni - Alimentatori / accessori - Staffe porta TV - Amplificazione stereo - Diffusori passivi / amplificati - Sicurezza



8015439012526