

SCHEDA TECNICA / TECHNICAL SHEET

DFS₆

Digital Feedback Suppressor - 6 mic processor







Useful in conference systems, churches or meeting halls, this fixture includes a sophisticated DSP processor and is capable of removing disturbing echo effect and audio feedback, which often take place when microphones are close to the speakers. These noises are sometimes caused by the simple touch of the hand on particularly sensitive microphones.

It supports 6 microphones (both unbalanced and with phantom power supply) but also 6 standard line signals

through 6,3mm connectors.

The operation system is quite easy: the signal from the amplifier is filtered, processed and sent back to the amplifier/ the speakers. During the signal processing the undesired high and low frequencies will be automatically cut off

| Line In: 1RCA MIC in: 6 XLR +6 Jack 6,3 LingeRutres1 RGA +2 XLR | Line: 20Hz - 20KHz - Shift: 150Hz -15KHz |
|-----------------------------------------------------------------|------------------------------------------|
| S/N ratio | >75dB |
| Rack space | 1U |
| Output connectors | XLR + RCA |
| Input connectors | XLR + jack 6,3mm |
| Power supply | 220V |
| Product dimensions | 484 x 55 x 220 mm |
| Weight | 3 kg |
| Color | black |

Karma Italiana srl si impegna affinchè le informazioni contenute in questa scheda siano le più precise possibili. Allo scopo di migliorare i propri prodotti, Karma Italiana si riserva il diritto di apportare modifiche ai propri prodotti senza alcun preavviso. Tutti i prodotti Karma sono conformi alle normative vigenti dell'Unione Europea.



